

TABLE TOP AUTOCLAVE SA-232X SERIES



CODE : ACL232X

FEATURES:

- Inexpensive, reliable, safe, easy operation and maintenance
- High efficiency for sterilizing wrapped/unwrapped/liquid/utensils, etc.
- Stainless steel sheathed heater for easy maintenance
- Versatile programs for selection:
 - Sterilization pressure adjustable from 0.9 – 2.1 kg per cm² assoc. with 115°C – 134°C
 - Preset sterilization time at 4 / 15 / 30 minutes depending on sterilization substances
- Microprocessor control operates sterilization automatically
- Sterilization starts timing only once set temperature is reached
- Complies with quality certifications and specifications of 93/42/EEC

SPECIFICATIONS :

MODEL :	232X Table top (Class II)
Actual Dimensions	510mm x 400mm x 540mm
Capacity	16 l
Chamber Size	230mm x 400mm (Depth)
Temperature / Pressure	Unwrapped / wrapped / liquid : 115°C -134°C ; 0.9-1.4kg per cm ²
Control System	Pressure control
Power Consumption	220-240V : 1.5kW ; 6.5Amp
Auto Drying	N/A
Pre-vacuum, Dry-vacuum	N/A
Indicators	Yes
Temperature Display	Temperature gauge
Sterilization Temp / Time	Wrapped: 121°C - 30 min; 134°C - 15 min Unwrapped: 121°C - 15 min; 134°C - 4 min
Standard Accessories	<ul style="list-style-type: none"> ✓ Sterilization box x 1 ✓ Tray x 1
Optional Accessories	<ul style="list-style-type: none"> ✓ Tray frame x 1 ✓ Tray x 3 ✓ Tray holder x 1 ✓ Spring x 2
Safety Devices	<ul style="list-style-type: none"> ✓ Over-heat shutout ✓ Safety valve ✓ Release valve ✓ Emergency exhaust valve ✓ Door safety holder ✓ Pressure control switch
Packaging Dimensions	640mm x 590mm x 480mm
Packaging Weight	40kg
Quality Standard	CE-MDD

BACK TO PRODUCT INDEX
BACK TO AUTOCLAVE/STERILISER INDEX PAGE